## **ARTICLE DATA SHEET**



Article : True® Dorval FR 32mm - Honeycomb Fabrics

Version : 2024-01

Semi-transparent fabric True® Dorval FR is made of post-consumer recycled polyester and beautifully filters the incoming day light. On top of the sustainable benefits of this fabric, this fabric is flame retardant according to the European B1 standard. Making this quality a truly unique product suitable for the residential as well as for the contract market. True® Dorval FR is also available as black-out fabric in eight timeless colours.

Composition : 85% Post- consumer recycled polyester/ 15% virgin polyester (PES)

Construction : spunlace non-woven fabric, film-laminated fabric

Transparency : semi-transparent

Oeko-Tex standard 100 certified : yes Flame retardant : yes Moisture resistant : yes PVC / Halogen free : yes

Customs code : 6307 9098

Preferential origin EU : no

Form of cell : D-shape Colour : Duo-Tone

 Cell size
 : 32 mm
 +/- 1,0 mm

 Plane range
 : visual plane
 +/- 1,0 mm

 Fabric width
 : 300 cm
 +/- 5 cm

 Fabric length
 : 15,73 meters
 +/- 10%

Weight per m2 : 151 g/m2 +/- 10% Material thickness : 0,19 mm +/- 10%

Colour fastness : 4-5 DIN EN ISO 105 B02 (blue scale 1-8)

Cupping : max. 2% Twisting : max. 2%

Labelling faults : indicated with a red label

Fault definition : any deviation in product and/or structure visible from 1 meter distance

Faults per package : max. 1 per 10 meters (on average)
Mutual fault distance : min. 2,5 meters between local faults

Pieces per packaging : max. 2 pieces with a min. length of 200 cells per piece

Fabric in packaging : room side up

Packaging : corrugated cardboard carton, fabric wrapped around in paper Batch identification : label on face side of packaging, label on front side of packaging

Total weight packaging : appr. 14,5 kg
Packaging dimensions : 3200 x 300 x 60 mm

Packing-list specification : article nr. / colour nr. / batch nr. / gross- and net linear meters / PO nr.

Storage and transport : horizontal

Cutting recommendation : guillotine cutter

Drilling recommendation : 3,5 mm diameter hollow drill

Text changes, technical modifications and misprints reserved. All our transactions are subject to our General Terms and Conditions that can be consulted free of charge on www.lienesch.com.