

ARTICLE DATA SHEET



Article : **True® Dorval FR 45mm - Honeycomb Fabrics**
Version : 2024-01

Semi-transparent fabric True® Dorval FR is made of post-consumer recycled polyester and beautifully filters the incoming day light. On top of the sustainable benefits of this fabric, this fabric is flame retardant according to the European B1 and C1 standards. Making this quality a truly unique product suitable for the residential as well as for the contract market. True® Dorval FR is also available as black-out fabric in eight timeless colours.

Composition : 85% Post- consumer recycled polyester/ 15% virgin polyester (PES)
Construction : spunlace non-woven fabric, film-laminated fabric
Transparency : semi-transparent

Oeko-Tex standard 100 certified : yes
Flame retardant : yes
Moisture resistant : yes
PVC / Halogen free : yes

Customs code : 6307 9098
Preferential origin EU : no

Form of cell : D-shape
Colour : Duo-Tone
Cell size : 45 mm +/- 1,0 mm
Plane range : visual plane +/- 1,0 mm
Fabric width : 366 cm +/- 5 cm
Fabric length : 17,5 meters +/- 10%

Weight per m2 : 151 g/m2 +/- 10%
Material thickness : 0,19 mm +/- 10%
Colour fastness : 4-5 DIN EN ISO 105 B02 (blue scale 1-8)

Cupping : max. 2%
Twisting : max. 2%

Labelling faults : indicated with a red label
Fault definition : any deviation in product and/or structure visible from 1 meter distance
Faults per package : max. 1 per 10 meters (on average)
Mutual fault distance : min. 2,5 meters between local faults

Pieces per packaging : max. 2 pieces with a min. length of 200 cells per piece
Fabric in packaging : room side up

Packaging : corrugated cardboard carton, fabric wrapped around in paper
Batch identification : label on face side of packaging, label on front side of packaging
Total weight packaging : appr. 18 kg
Packaging dimensions : 3800 x 350 x 68 mm
Packing-list specification : article nr. / colour nr. / batch nr. / gross- and net linear meters / PO nr.
Storage and transport : horizontal

Cutting recommendation : guillotine cutter
Drilling recommendation : 3,5 mm diameter hollow drill

Text changes, technical modifications and misprints reserved. All our transactions are subject to our General Terms and Conditions that can be consulted free of charge on www.lienesch.com.