## **ARTICLE DATA SHEET**

## honeycell

## Article:True® Rioja 25 mm - Honeycomb FabricsVersion:2024-01

Semi-transparent Honeycell fabric True® Rioja is the perfect choice when maximum functionality is required. Due to the honeycomb structure, this non-woven fabric has excellent insulating properties ensuring the heat to stay outside during summer and inside during winter. Rioja is available in sixteen colours.

| Composition<br>Construction<br>Transparency | :<br>:<br>: | 80% Post-consumer recycled polyester / 20% Polyester (PES)<br>spunlace non-woven fabric<br>semi-transparent |  |  |
|---|-------------|---|--|--|
| Oeko-Tex standard 100 certified             | :           | yes   |  |  |
| Flame retardant                             | :           | no  |  |  |
| Moisture resistant                          | ÷           | yes   |  |  |
| PVC / Halogen free                          | :           | yes   |  |  |
| Customs code                                | :           | 6307 9098   |  |  |
| Preferential origin EU                      | :           | no  |  |  |
| Form of cell                                | :           | D-shape   |  |  |
| Colour                                      | :           | Duo-Tone  |  |  |
| Cell size                                   | :           | 25,4 mm   | +/- 1,0 mm                                 |  |
| Fabric width                                | :           | 300 cm  | +/- 5 cm                                   |  |
| Fabric length                               | :           | 12,4 meters   | +/- 10%                                    |  |
| Weight per m2                               | :           | 164 g/m2  | +/- 10%                                    |  |
| Material thickness                          | :           | 0,24 mm   | +/- 10%                                    |  |
| Colour fastness                             | :           | 7   | DIN EN ISO 105 B02 (blue scale 1-8)        |  |
| Cupping                                     | :           | max. 2%   |  |  |
| Twisting                                    | :           | max. 2%   |  |  |
| Labelling faults                            | :           | indicated with a red  | d label                                    |  |
| Fault definition                            | :           | any deviation in product and/or structure visible from 1 meter distance                                     |  |  |
| Faults per package                          | :           | max. 1 per 10 meters (on average)   |  |  |
| Mutual fault distance                       | :           | min. 2,5 meters between local faults  |  |  |
| Pieces per packaging                        | :           | max. 2 pieces with a min. length of 200 cells per piece   |  |  |
| Fabric in packaging                         | :           | room side up  |  |  |
| Packaging                                   | :           | corrugated cardboa  | ard carton, fabric wrapped around in paper |  |
| Batch identification                        | :           | label on face side of packaging, label on front side of packaging   |  |  |
| Total weight packaging                      | :           | appr. 12,0 kg   |  |  |
| Packaging dimensions                        | :           | 3180 x 340 x 50 mm  |  |  |
| Packing-list specification                  | :           | article nr. / colour nr. / batch nr. / gross- and net linear meters / PO nr.                                |  |  |
| Storage and transport                       | :           | horizontal  |  |  |
| Cutting recommendation                      | :           | guillotine cutter   |  |  |
| Drilling recommendation                     | :           | 3,5 mm diameter hollow drill or 3,0 mm diameter spiral drill  |  |  |

Text changes, technical modifications and misprints reserved. All our transactions are subject to our General Terms and Conditions that can be consulted free of charge on www.lienesch.com.